



ADJUSTABLE ULTRA LOW GLARE LED DOWNLIGHT



AXEL

The Lumax low glare tilt adjustable downlight suitable for residential and commercial applications minimising direct glare whilst still providing even and effective illumination and wall washing.

Colour selection via 3 CCT switching with integral flicker free on board integral driver. Perfect smooth phase dimming to create required lighting levels.

3CCT SWITCHABLE COLOUR TEMPERATURE



Lumax	AXEL
Input	240V
Body	Thermo Plastic
Colour Trim	Matt White/Black
Tilt Angle	45°
Driver	Integral Non Flicker
Connection	0.6m Flex & plug
LED Diodes	COB
Beam Angle	60°
Wattage	9W
Lumen Output	800lm
Power Factor (PFC)	0.9
Colour Rendering Index (CRI)	>85
CCT Selection	3CCT via switch
Correlated Colour Temp (CCT)	3000K, 4000K, 5000K
Cut out	90mm
Height	85mm
Overall diam	105mm
Operating Temp. Range	-20 +50deg
Flex & Plug	Included
Warranty	3 Years



FITTING COLOURS

BLACK WHITE

INPUT VOLTAGE
240V



OUTPUT POWER
9W



LUMENS
800



CUT HOLE
90MM



COL TEMP
3,000K
4,000K
5,000K



WARRANTY
3 YEARS

