

LED BATTEN 3CCT SELECT

BTN340 / BTN360

The Lumax batten is an economical replacement for traditional fluorescent battens.

Able to be directly mounted to the ceiling and offering centre cable entry or through wiring to suit most applications.

Fitted with a shatterproof opal polycarbonate diffuser for wide and even lighting distribution.

The BTN series provides a flicker free lighting environment, with 3 colour selector switch and is suitable for most indoor applications.

Very simple installation and fitted with an efficient and reliable Tridonic driver.



Lumax	BTN340	BTN360
Input	240V	
Body	Steel White paint	
Diffuser	Polycarbonate UV resistant	
Driver	Tridonic	
LED Diodes	Epistar	
Beam angle	120 deg	
Wattage	40W	60W
Amps	0.2A	0.3A
Lumen output	4000lm	6000lm
Power Factor (PFC)	>.90	
CRI (Colour Rendering Index)	>80+	
CCT (Correlated Colour Temp)	3000K/4000K / 6500K	
IP Rating	IP20	
Dimensions	1200x72x72	1500x72x72
Cable entry	Centre entry/through wiring	
Gear tray	White steel	
Operating Temp range	-20+40 deg	
Electrical Class	Class I	
Warranty	5 years	

FITTING COLOURS:

White

INPUT VOLTAGE
240V



OUTPUT POWER
BTN340 **40W**
BTN360 **60W**



LUMENS
BTN340 **4,000**
BTN360 **6,000**



COL TEMP
3,000K
4,000K
6,500K



WARRANTY
5 YEARS

