



## LED DOWNLIGHT

### DL312T

Suitable for all residential and commercial applications where high quality, excellent colour rendering and reliable lighting is required.

Very shallow recessing depth of only 47mm. Able to be covered by thermal insulation meeting IC-F and IC-4 standards and easy to install.

The remote driver is fitted, with a flex and plug for ease of installation. The ThermoPlastic used in the housing and flange is suitable for under eaves and is resistant to salt air degradation.

Tilting to 20° for sloping ceilings.



### LED COLOUR TEMPERATURE CHANGING

SWITCH ON BACK OF LIGHT FITTING



FITTING COLOURS:

White

Black

Lumax	DL312T
Body	ThermoPlastic
Diffuser	PC Opal
Driver	Remote
- Soft Start	✓
- Overload Protection	✓
- Short Circuit Protection	✓
LED Diodes	Epistar SMD 2835
Beam angle	120 deg
Tilt angle	40 deg
Wattage	10 Watt
Dimmable	Phase cut-off
Lumen output	900lm
Power Factor (PFC)	>.90
CRI (Colour Rendering Index)	>85+
CCT (Correlated Colour Temp)	3000K / 4000K / 6500K
IP Rating (Below Ceiling)	IP20
Cut out	90mm
Height	35mm
Overall diam	110mm
Operating Temp range	-20+50 deg
Electrical Class	Class II
Flex & Plug	Included
Warranty	5 years

INPUT VOLTAGE  
**240V**



OUTPUT POWER  
**10W**



LUMENS  
**900**



ADJ COL TEMP  
**3,000K**  
**4,000K**  
**6,500K**



DIMMABLE  
**YES**



CUT HOLE  
**90MM**



WARRANTY  
**5 YEARS**

