

LED DOWNLIGHT

3CCT HIGH OUTPUT

DL313



Suitable for all residential and commercial applications where high quality, excellent colour rendering and high light output is required.

Very shallow recessing depth of only 35mm. Able to be covered by thermal insulation meeting IC-F and IC-4 standards and easy to install.

The remote driver is fitted, with a flex and plug for ease of installation. Very high lumen output suitable for high ceiling installations. The ThermoPlastic used in the housing and flange is suitable for under eaves and is resistant to salt air degradation.



FITTING COLOURS:

White


LED COLOUR TEMPERATURE CHANGING



INPUT VOLTAGE
240V 

OUTPUT POWER
10W 

LUMENS
1100 

ADJ COL TEMP
3,000K
4,000K
6,500K 

DIMMABLE
YES 

CUT HOLE
90MM 

WARRANTY
5 YEARS 

Lumax	DL313
Body	ThermoPlastic
Diffuser	PMMA Opal
Driver	Remote
- Soft Start	✓
- Overload Protection	✓
- Short Circuit Protection	✓
LED Diodes	SMD 2835
Beam angle	120 deg
Wattage	10 Watt
Dimmable	Phase cut-off
Lumen output	1100lm
Power Factor (PFC)	>.90
CRI (Colour Rendering Index)	>85+
CCT (Correlated Colour Temp)	3000K / 4000K / 6500K
IP Rating (Below Ceiling)	IP65
Cut out	90mm
Height	35mm
Overall diam	106mm
Operating Temp range	-20+50 deg
Electrical Class	Class II
Flex & Plug	Included
Warranty	5 years