

# HIGH POWERED LED HIGHBAY

## HYBE300 / HYBE400

Perfect for very high ceiling heights or for high lighting levels.

These highbays are the at the leading edge of industrial lighting performance and controls.

A cost-effective solution that will return substantial energy savings and CO2 emissions as well as providing the optimum lighting levels and visual comfort required.

Suitable for instant switching in conjunction with motion sensors or daylight harvesting controls.

Available with DALI or 1-10V dimming on request



FITTING COLOURS:  Blk

Lumax	HYBE300	HYBE400
Material	ADC12 Aluminium	
Driver	Constant Current	
LED Diodes	SMD 2835	
Wattage	300W	400W
Efficiency	140Lm/W	
Lumen output (actual)	42,000Lm	56,000Lm
Power Factor (PFC)	0.9	
CRI (Colour Rendering Index)	Ra80	
CCT (Correlated Colour Temp)	5000K	
Beam angle	110deg	
IP Rating	IP65	
IK Rating	IK09	
Diameter	350mm	400mm
Weight	4.9Kg	
Current	1.25Amps	1.7Amps
Flex and plug	1.5M	
Suspension hook	Included	
Operating Temperature	-30°C to +45°C	
Electrical Class	Class I	
Surge Protection	6kV	
Warranty	5 Years	

WATTAGE

HYBE300 **300W**

HYBE400 **400W**



LUMENS

HYBE300 **42,000**

HYBE400 **56,000**



COL TEMP

**5,000K**



SIZE (MM)

HYBE300 **350**

HYBE400 **400**



**FLEX  
& PLUG**



WARRANTY

**5 YEARS**

