

PETE

The IP65 protected wide body weatherproof luminaire ideal for internal or external use in corrosive, wet or dirty atmospheres, and is suitable for surface or pendant mounting.

The luminaire employs an impact resistant polycarbonate body and a clear polycarbonate diffuser. Opal diffusers are available as a separate part (PTEOP).

Stainless steel diffuser retaining toggles, and the stainless steel mounting clips are supplied as standard and negate the need for drilling into the luminaire body, thus maintaining the integrity of the IP65 rating.

Suitable for residential, commercial and industrial applications.

Featuring the best LED Tridonic Driver available in the market for long service life and efficency.

A 3 CCT colour selector switch is provided to enable quick colour temperature output setting on installation.





Body	Polycarbonate UV resistant	FITTING COLOURS:
Diffuser	Polycarbonate UV resistant/Clear	White
Driver	Tridonic	

INPUT VOLTAGE 240V

POWER



LUMENS CLEAR 6,590



COL TEMP

4,000K 5,000K 6,000K



LENGTH (MM) 1565



WARRANTY **5 YEARS**



Body	Polycarbonate UV resistant
Diffuser	Polycarbonate UV resistant/Clear
Driver	Tridonic
LED Diodes	Epistar
Wattage	60W
Amps	0.27A
Lumen output	6590lm
LED Qtys	216PCS
Power Factor (PFC)	>.95
CRI (Colour Rendering Index)	>80+
CCT (Correlated Colour Temp) 3CCT	4000K / 5000K / 6000K
IP Rating	IP65
IK Rating	O8
Dimensions	1565x130x92
Gasket	Silicon
Cable entry gland	Included
Clips	Stainless steel 10pcs
Mounting hardware	Stainless steel
Gear tray	White c/w lanyard
Operating Temp range	-30 – +45°C
Weight	2.0Kg
Electrical Class	Class I
Warranty	5 years