

NARROW BODY LED **WEATHERPROOF**

SLIM 39 & 55

The SLIM range comprises IP65 protected weatherproof luminaires ideal for internal or external use in corrosive, wet or dirty atmospheres, and is suitable for surface or pendant mounting. A very narrow body luminaire suitable for most residential, commercial and industrial applications. Stainless steel diffuser retaining toggles, and the stainless steel mounting clips are supplied as

standard and negate the need for drilling into the luminaire body, thus maintaining the integrity of the IP65 rating.



Electrical Class

Warranty



Lumax	SLIM 39	SLIM 55
Body	Polycarbonate UV resistant	
Diffuser	Opal	Clear
Driver	Tridonic	
LED Diodes	Epistar	
Wattage	39W	55W
Amps	0.2A	0.23A
Lumen output	5000lm	6600lm
LED Qtys	182PCS	216PCS
Power Factor (PFC)	>.95	
CRI (Colour Rendering Index)	>80+	
CCT (Correlated Colour Temp)	5000K	3000/4000/6500k
IP Rating	IP65	
IK Rating	0	
Dimensions	1265x90x92	1565x90x92
Gasket	Silicon	
Cable entry gland	Included	
Clips	Stainless steel 10pcs	Stainless steel 12pcs
Mounting hardware	Stainless steel	
Gear tray	White c/w lanyard	
Operating Temp range	-30 − +45°C	
Weight	1.4Kg	1.8Kg





OUTPUT POWER

SI IM 39 39W **SLIM 55 55W**



LUMENS SLIM 39 5,000



LENGTH (MM)

SLIM 39 **1265** SLIM 55 **1565**



WEIGHT (KG)

SLIM 39 **1.4**

SLIM 55 1.8



WARRANTY 3 YEARS



Class I

3 years