

ULTRA LOW GLARE LED DOWNLIGHT

BERNIE

The Lumax low glare downlight suitable for residential and commercial applications minimising direct glare whilst still providing even and effective illumination.

Colour selection via 3 CCT switching with integral flicker free on board integral driver. Perfect smooth phase dimming to create required lighting levels



Lumax	BERNIE
Input	240V
Body	Thermo Plastic
Colour Trim	Matt White/black
Driver	Integral Non Flicker
Connection	0.6m Flex & plug
LED Diodes	COB
Beam Angle	60 degree
Wattage	8.5W
Lumen Output	800lm
Power Factor (PFC)	0.9
Colour Rendering Index (CRI)	>85
CCT Selection	3CCT via switch
Dimmable	Yes
Correlated Colour Temp (CCT)	3000K, 4000K, 5000K
IP Rating (Below)	IP44
Cut out	90mm
Height	90mm
Overall diam	100mm
Operating Temp. Range	-20 +50deg
Flex & Plug	Included
Warranty	3 Years

FITTING COLOURS

BLACK  WHITE 

INPUT VOLTAGE
240V



OUTPUT POWER
8.5W



LUMENS
800



CUT HOLE
90MM



COL TEMP
3,000K
4,000K
5,000K



WARRANTY
3 YEARS

